

SCORPIO-T



eFFINION
DECASITE
SCORPIO-T

KEY BENEFITS:

- Die-cast aluminum housing with modular design, corrosion resistant
- High uniformity LED optics constructed of durable polycarbonate
- Over 20 optical lenses available
- 120-277VAC and 347-480VAC
- Optional emergency power supply
- UL/CUL/LM79/CB/CE/RoHS/IK08 certifications
- Outdoor IP67 rated
- Available in Grey, Black, Bronze or White
- 10 year limited warranty



ADVANTAGES:



10 Year Warranty

No hassle returns and warranty for 10 years.



Quality Componentry

Fully tested and approved internal components.



Modular Design

Connect with other Efficion fixtures, or other accessories.



Smart Lenses

Get perfect light output control, with lenses that shape light, not cut it.



Protective Coating

Keep your components safe from weather and corrosion.



Easy Install

Stop spending precious hours installing.

SPECS:

Power	30-320W
Input	120-277VAC / 220-240VAC / 347-480VAC
PF	>0.95
THD	<20%
L85	>60,000H
Operating Temp.	-40°C~+50°C
Efficacy	120-140 lm/W
ANSI CCT	3000K / 4000K / 5000K / 5700K
Min. CRI	70 / 80 / 85

IP Rating	IP67
SPD	Optional
Certifications	UL/CUL/LM79/SAA/ENEC/CB/CE/ERP/ROHS/IK08
DALI	Optional
1-10V	Optional
Photocell	Optional
Smart Control	Optional
Optic (IESNA)	Type I / Type II / Type III / Type IV / Type V
Color Options	Grey / Black / Bronze / White



eFFINION SCORPIO-T

eFFINION

DECASITE

SCORPIO-T

Model No.	System Power	Voltage	Drive Current	Luminous Flux		Efficacy(lm/W)
				3000K	4000K/5000K	
SCPA30-T	33W	120-277VAC	530mA	3564lm	3960lm	120
SCPB40-T	42W	120-277VAC	700mA	4347lm	4830lm	115
SCPA60-T	64W	120-277VAC	530mA	6912lm	7680lm	120
SCPB80-T	84W	120-277VAC	700mA	8694lm	9660lm	115
SCPC80-T	84W	347-480VAC	700mA	8694lm	9660lm	115
SCPA90-T	92W	120-277VAC	530mA	10350lm	11500lm	125
SCPB120-T	125W	120-277VAC	700mA	13500lm	15000lm	120
SCPC120-T	125W	347-480VAC	700mA	13500lm	15000lm	120
SCPA120-T	121W	120-277VAC	530mA	13613lm	13613lm	125
SCPB160-T	166W	120-277VAC	700mA	17928lm	17928lm	120
SCPC160-T	166W	347-480VAC	700mA	17928lm	17928lm	120
SCPA150-T	151W	120-277VAC	530mA	16988lm	18875lm	125
SCPB200-T	205W	120-277VAC	700mA	22140lm	24600lm	120
SCPC200-T	205W	347-480VAC	700mA	22140lm	24600lm	120
SCPA180-T	182W	120-277VAC	530mA	20475lm	22750lm	125
SCPB240-T	246W	120-277VAC	700mA	26568lm	29520lm	120
SCPC240-T	246W	347-480VAC	700mA	26568lm	29520lm	120
SCPA210-T	211W	120-277VAC	530mA	23738lm	26375lm	125
SCPB280-T	285W	120-277VAC	700mA	30780lm	34200lm	120
SCPC280-T	285W	347-480VAC	700mA	30780lm	34200lm	120
SCPA240-T	240W	120-277VAC	530mA	27000lm	30000lm	125
SCPB320-T	323W	120-277VAC	700mA	34884lm	38760lm	120
SCPC320-T	323W	347-480VAC	700mA	34884lm	38760lm	120
SCPA270-T	267W	120-277VAC	530mA	31239lm	34710lm	130
SCPA300-T	296W	120-277VAC	530mA	34632lm	38480lm	130

REV: 170609

